

Declaration of Performance

DOP/CE/9054

Low Voltage Junction Box – 104 - Chamber
Ballinamere, Tullamore, Co. Offaly



1. **Unique Identification code of the product - type:** Code – 9054 – Low Voltage Junction Box- 104 - Chamber

2. **Intended use:** Reinforced Precast Component for use as an inspection Chamber

3. **Manufacturer:** Creative Concrete, Ballinamere, Tullamore, Co. Offaly

4. **Authorised Representative:** N/A

5. **System of AVCP:** System 4

6. **Harmonised Standard:** EN 1917:2002&AC:2008 **Notified body:** N/A

7. Declared Performance

Characteristic	Declared Performance	Provisions to Annex ZA (informative) of I.S EN 1917:2002
Watertightness:	No Leakage of joint or unit at 30kPa (0,3) bar internally	4.3.8
Mechanical resistance:	Vertical Strength 400kN	4.3.5
Opening Size:	(LN x WN) 750mm, 675mm Rectangular	4.3.3.5
Durability:	Adequate for normal serviceability conditions	4.3.10

8. N/A

<https://creativeconcrete.ie>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Chris O'Reilly, Technical & Production Manager, Creative Concrete, Ballinamere, Tullamore, Co. Offaly

Date: 02nd September 2022



Creative Concrete

17

EN 1917:2002&AC:2008
Low Voltage Junction Box – 104 - Chamber
(LxWxH)1000mm, 925mm, 1025mm

1. **Unique Identification code of the product - type:** Code – 9054 – Low Voltage Junction Box- 104 - Chamber
2. **Intended use:** Reinforced Precast Component for use as an inspection Chamber
3. **Manufacturer:** Creative Concrete, Ballinamere, Tullamore, Co. Offaly
4. **Authorised Representative:** N/A
5. **System of AVCP:** System 4
6. **Harmonised Standard:** EN 1917:2002&AC:2008 **Notified body:** N/A

Watertightness	Declared Value	No Leakage of joint or unit at 30kPa (0,3 bar) internally
Mechanical Resistance	Declared Value	Vertical Strength 400kN
Opening Size	Declared Characteristic	(LN x WN) 750mm, 675mm Rectangular
Durability	Declared Performance	Adequate for normal serviceability conditions



Signed for and on behalf of the manufacturer by:

Chris O'Reilly, Technical & Production Manager, Creative Concrete, Ballinamere, Tullamore, Co. Offaly

Date: 02nd September 2022